

MARCHESAN

6009 ATCR

WHEEL TYPE OFFSET DISK HARROW



THE BRAND OF THE LAND

The model 6009 ATCR - Wheel Type Offset Disk Harrow, because of its light and smaller diameter disc blades, is ideally suited for soil preparation and levelling of large crop areas after the harvest. After the last ratoon crop of sugar cane, the 6009 ATCR will efficiently incorporate heavy stubble into the soil, speeding up its decay thereby increasing soil fertility.


Standard Features:

- Heat treated steel notched disc blades.
- Rugged 1.5/8" round, heat treated alloy, steel disc gang axles.
- Cast iron disc spacer spools.
- Adjustable working position.
- Rugged built frame and gang carriers.
- Adjustable disc gang angles.
- Stabilizer bar for front and rear disc gangs leveling.
- Adjustable heavy duty disc scrapers.
- Greasable or oil bath disc gang bearing assemblies.
- Hydraulic controlled depth gauge wheels.
- Adjustable drawbar, drawbar plates and offset bar.
- Standard tool kit.



Cylinder lock for safety transportation.

RUGGEDLY BUILT FOR LONGER LIFE



TAPERED BEARINGS AND DUO-CONE TYPE SEALS.



SPECIAL OIL BATH BEARING ASSEMBLIES

THE LIFE OF YOUR DISK HARROW. REQUIRES ORIGINAL TATU REPLACEMENT PARTS.

TECHNICAL SPECIFICATIONS:

Model	Number of Disc Blades	Working Width ft. in. (mm)	Disc Blades		Weight per Disc lbs (Kg)	Approx. Net Weight* lbs (Kg)	Tractor Draw Bar Horse Power
			Dimensions	Spacing			
6009 ATCR	12	4' 2" (1,270)	24"x6.0mm, 26"x6.0mm, 28"x6.0mm or 28"x7.5mm	9" (230mm)	260 (118)	3,126 (1,418)	70 - 75
	14	4' 11" (1,500)			241 (109)	3,375 (1,531)	75 - 80
	16	5' 8" (1,730)			225 (102)	3,600 (1,633)	80 - 90
	18	6' 5" (1,960)			235 (107)	4,243 (1,925)	95 - 100
	20	7' 2" (2,190)			223 (101)	4,473 (2,029)	105 - 120
	22	7' 11" (2,420)			215 (98)	4,742 (2,151)	125 - 140
	24	8' 8" (2,650)			212 (96)	5,090 (2,309)	140 - 160
	26	9' 5" (2,880)			204 (93)	5,317 (2,412)	160 - 170
	28	10' 2" (3,110)			197 (89)	5,522 (2,505)	170 - 180
	32	11' 8" (3,570)			261 (118)	8,373 (3,798)	180 - 190
	36	13' 2" (4,030)			239 (108)	8,624 (3,912)	200 - 220
	40	14' 8" (4,490)			223 (101)	8,913 (4,043)	230 - 240
	44	16' 2" (4,950)			212 (96)	9,332 (4,233)	240 - 260

* Approx. net weight with 26" x 6.0mm disc blades.

> Axle Size: 1.5/8" (41.28mm). > Approx. depth of cut: 4" to 7" (100 - 180mm).

MARCHESAN IMPLEMENTOS E MÁQUINAS AGRÍCOLAS TATU S.A.

Av. Marchesan, 1979 | CEP CODE 15994-900 | Phone: +55 16 3382.8282 | Matão-SP-Brasil | CNPJ.: 52.311.289/0001-63 | Inscr. Est.: 441.000.151.114

MARCHESAN S.A. reserves the right to perfect or alter the characteristics of its products, without the obligation to do so with those already marketed and without giving prior knowledge. The photos and drawings are merely illustrative. Rev. 07 - 10/2020

www.marchesan.com.br

