

# **6010 GAICR**

## WHEEL OFFSET DISK HARROW



THE BRAND OF THE LAND

The model 6010 GAICR-Wheel Offset Disk Harrow, is specially designed to operate with wheel or crawler tractors. It is ideally suited for tough plowing jobs found in new cleared forest areas or heavy sugar cane stubble left after the last ration crop.

All models have hydraulic controlled depth gauge and transport wheels, which make them more maneuverable and easier to transport to other fields.

# GAICR

### **Standard Features:**

- Welded and rugged tubular steel frames.
- Stabilizer bar for front and rear disc gangs leveling.
- Disc gang angle adjusted mechanically.
- Perforated offset bar to allow lateral drawbar adjustments under varying draft conditions.
- Box type construction drawbar with standard drawbar plates.
- Hydraulic controlled depth gauge and transport wheels mounted to wheel hubs that have greasable tapered roller bearings.
- Double acting hydraulic cylinders with hoses and quick couplers.
- Rugged 1.5/8" round, heat-treated steel alloy disc gang axles.
- Greasable or oil bath disc gang bearing assemblies.
- Cast iron disc spacer spoos.
- Heavy duty disc blade scraper.
- Standard tool kit



SPECIAL OIL BATH BEARING ASSEMBLIES



THE LIFE OF YOUR DISK HARROW

### **TECHNICAL SPECIFICATIONS:**

Model	Number of Disc Blades	Working Width ft. in. (mm)	Disc Blades		Weight per Disc		Approx. Net Weight*		Tractor Draw Bar
			Dimensions	Separación	lbs (Kg)	lbs	(Kg)	Horse Power	
6010 GAICR	12	5′3″ (1,600)	26"x6.0 mm 28"x6.0 mm or 28"x7.5mm	10.5/8" (270mm)	292	(132)	3,505	(1,590)	70 - 80
	14	5′9″ (1,750)			254	(115)	3,564	(1,617)	80 - 90
	16	6'7" (2,000)			266	(121)	4,268	(1,936)	100 - 110
	18	7′7″ (2,300)			252	(114)	4,548	(2,063)	110 - 120
	20	8′5″ (2,570)			247	(112)	4,953	(2,247)	120 - 135
	22	9'4" (2,840)			237	(107)	5,231	(2,373)	135 - 150
	24	10'2" (3,110)			233	(105)	5,601	(2,541)	150 - 165
	26	11'1" (3,380)			218	(99)	5,672	(2,573)	165 - 180
	28	11'12" (3,650)			213	(97)	5,985	(2,715)	180 - 195
	30	12′10″ (3,920)			218	(99)	6,554	(2,973)	195 - 210
	32	13'9" (4,180)			259	(118)	8,304	(3,767)	210 - 230
	36	15'6" (4,720)			248	(112)	8,931	(4,051)	230 - 250
	40	17'3" (5,250)			242	(110)	9,674	(4,388)	250 - 270
	44	17′10″ (5,440)	28″x7.5mm		261	(118)	11,488	(5,211)	270 - 290
	48	20'5" (6,230)			250	(113)	12,017	(5,451)	290 - 310

<sup>\*</sup> Approx. net weight with 28" x 7.50mm disc blades.

### **MARCHESAN - TATU PRODUCTS**

Av. Marchesan, 1979 | CEP 15994-900 | Phone: +55 (16) 3382.8282 | Matão-SP-Brasil | CNPJ.: 52.311.289/0001-63 | Inscr. Est.: 441.000.151.114







<sup>&</sup>gt; Depth of cut: 4.3/4" to 7.7/8" (120 to 200mm)