

# **6011 GAICR 300**

WHEEL OFFSET DISK HARROW



WORKING WIDTH  
6 TO 11 FT.

**THE BRAND OF THE LAND**





**MARCHESAN**

The model **6011 GAICR 300** is specially designed to offer maximum working width and weight per blade for medium horsepower tractors. Ideal for soil preparation, primary tillage in grassland and leveling of large crop areas after harvesting.



### Standard Features:

- Welded and rugged tubular steel frame and gang carriers.
- Stabilizer bar for front and rear disc gangs leveling.
- Disc gang angle adjusted mechanically.
- Heat treated boron steel disc blades, notched front and rear.
- Adjustable drawbar - able to offset the machine.
- Hydraulic controlled depth gauge and transport wheels.
- Double acting hydraulic cylinder with hoses and quick couplers.
- Rugged 1.3/4" round, heat-treated steel alloy disc gang axles.
- Cast iron disc spacer spools.
- Tatu oil bath bearing assemblies with tapered roller bearings, duo-cone seals.
- Recommended two single 600x16 - 6 ply rib implement tires for 14 blades.
- Recommended two dual 750x16 - 10 ply rib tires for 16 to 26 blades.
- Furrow filler blade (optional).
- Stone guards (optional).



### Notched disc blades

are produced with rigorous standards, they offer superior resistance to the wearing and impacts

### Specifications:

Model	Number of Disc Blades	Working Width ft. in. (mm)	Disc Blades		Weight per Disc lbs (Kg)	Approx. Net Weight* lbs (Kg)	Tractor Draw Bar Horse Power
			Dimensions	Spacing			
6011 GAICR 300	14	6' 3" (1,900)			273 (124)	3,833 (1,739)	90 - 105
	16	7' 2" (2,185)			292 (132)	4,676 (2,121)	105 - 115
	18	7' 10" (2,400)	26"x6.0mm,		286 (130)	5,154 (2,338)	115 - 125
	20	9' (2,735)	28"x6.0mm,	11.13/16"	279 (127)	5,595 (2,538)	125 - 140
	22	9' 10" (3,010)	28"x7.5mm	(300mm)	267 (121)	5,888 (2,671)	140 - 155
	24	10' 9" (3,280)	or		258 (117)	6,192 (2,809)	155 - 170
	26	11' 8" (3,560)	30"x7.5mm		249 (113)	6,452 (2,927)	170 - 185
	28	12' 7" (3,840)			245 (111)	6,876 (3,119)	185 - 200
	30	13' 6" (4,120)			246 (112)	7,398 (3,356)	200 - 215

\* Approx. net weight with 26" x 6.0mm disc blades. | Depth of cut: 5.15/16" to 8.5/8" (150 to 220mm).

MARCHESAN S.A. reserves the right to perfect or change the characteristics of its products, without prior notice and without the obligation to proceed with those already marketed. The photos are only illustrative. 12/2018 - Rev. 01

### MARCHESAN IMPLEMENTOS E MÁQUINAS AGRÍCOLAS TATU S.A.

Av. Marchesan, 1979 - CEP 15994-900 - Matão-SP-Brasil

Phone: +55 16 3382.8282 - Fax (Sales): 3382.8297

CNPJ.: 52.311.289/0001-63 - Inscr. Est.: 441.000.151.114

[www.marchesan.com.br](http://www.marchesan.com.br)

email: [tatu@marchesan.com.br](mailto:tatu@marchesan.com.br)



**THE BRAND OF THE LAND**