

Planters

Implements

Disc Blades

Tillage
Tools



MARCHESAN

AAR

Two-way Moldboard Plow



- ▶ *HORIZONTAL SWITCHING*
- ▶ *SIMETRIC MOLDBOARD 24"*

Easy Maneuverability - Excellent Trash Covering



- Heavy duty welded frame constructed with plow steel for extra strength and rigidity.
- Hydraulic Switching System: quick reversion of the moldboards through a double action hydraulic cylinder with check valve for extra safety and locking position.
- Three Point Hitch: equipped with category II brackets for universal three point linkage.
- Horizontal Levelling System: levelling of the plows is done with another hydraulic cylinder acting in conjunction with the switching operation.

SPECIFICATIONS

Model	Number of Bottoms	Working With ft.in. (mm)	Spacing in (mm)	Approx. Net Weight in (mm)	Tractor HP Required
AAR	03	4' 5" (1,350)		2,380 (1,082)	120
	04	5' 11" (1,850)	28" 710	2,728 (1,240)	140
	05	7' 5" (2,250)		3,080 (1,400)	160

- Depth of Cut: 15.3/4" (400mm) - Clearance: 32" (820mm)



- Cylindrical Moldboards layered with high density polyethylene plate for better soil scouring.
- Plowshare made with alloy steel for wear resistance and longer positive penetration. Optional Plowshare chrome alloy tip, recommended only for highly abrasive sandy soils.
- Shear-bolt to protect each plow bottom.
- Adjustable depth control wheel made with segmented tire.

Planters

Implements

Disc Blades

Tillage
Tools



MARCHESAN

MARCHESAN - TATU PRODUCTS

Av. Marchesan, 1979 - P.O. Box 131 - ZIP 15994-900 - Matão-SP-Brazil

Fone: (55) 16 3382-8282 - Fax: (55) 16 3382-1003 / 3382-1009

www.marchesan.com.br e.mail: tatu@marchesan.com.br

MARCHESAN S.A. reserves the right to improve or modify its products, changing the specifications, without previous notice. - 11/2006 - Edition 03