


# TSTA

LEVEE TERRACING PLOW



THE BRAND OF THE LAND



## TSTA

### LEVEE TERRACING PLOW

Building an average 600 – 800 meters of terrace per hour, the use of TSTA allows to keep the fertile layer of soil with total area usage for planting.





#### **FEATURES**

- High resistance structure.
- Less weight and more versatility in the operations.
- The tapered disc blades to the terrace elevation, as well as the transport wheel activation are done by double action hydraulic cylinders with precise movements which are hydraulically controlled from the tractor driver's seat.
- Pulled by drawbar, leaving the three point hitch free.
- The wheel system with two 750 x 16 tyres, making the transport and manoeuvring easier also when controlling the working depth.
- Disc gangs with oil bath bearings or greasable bearings.
- Floating guide wheel that absorbs the side shocks keeping the implement to the right alignment.

Tapered roller bearings and Duo-Cone seals.



THE LIFE OF YOUR DISK HARROW REQUIRES ORIGINAL TATU REPLACEMENT PARTS.

Tatu bearing assemblies with roller bearings, grease lubricated (CM) or in permanent oil lubrication - DUROMARK ® (DM).

#### **TECHNICAL SPECIFICATIONS**

Model	Nº of Discs	Terrace Dimentions Height x Width*	DISCS		Net Weight	** Tractor Draw
			Dimension	Spacing	(Kg)	Bar Horse Power
TSTA	14	1,20m x 5,20m			1967	85
	16	1,20m x 5,80m			2190	100
	18	1,20m x 6,40m	Ø 26"x6,00mm	400mm	2299	120
	20	1,20m x 7,00m			2464	140
	22	1,20m x 7,60m			2573	160

\* Maximum dimensions before finishing. \*\* Minimum power required. Transport width: 3000mm

MARCHESAN S.A. reserves the right to perfect or change the characteristics of its products, without prior notice and without the obligation to proceed with those already marketed.

The photos are only illustrative. 10/2018 - Rev. 01







Av. Marchesan, 1979 - CEP 15994-900 - Matão-SP-Brasil Phone: +55 16 3382.8282 - Fax (Sales): 3382.8297 CNPJ.: 52.311.289/0001-63 - Inscr. Est.: 441.000.151.114